


TILER      DRYWALLER      HOUSE PAINTER      MASON      FACADE INSTALLER      ROOFER      FLOORING INSTALLER      LANDSCAPER

## POLYPERFOR - Punching machine

Ref. : 018555  
Gencod 3476060001856  
UPC: 5



Sheet metal and slate.  
Punching power : 740 kg.  
Supplied with 5 punches :  
Ø 3.3 mm for sheet metal + Ø 3.3 mm for slate.  
Ø 4.1 mm for steel suspension wires.  
Ø 4.9 mm and 6.2 mm for threaded rod.  
Precise graduation opening to max. 8 mm.  
Adjustable depth guide up to 43 mm.  
Applications : roofing, suspended ceilings etc.



DIAMÈTRE DU PIONNEAU	DE LA FUSÉE	DE LA BÂTE	DE LA BÂTE	DE LA BÂTE
Ø 3.3 mm	Ø 3.3 mm	Ø 3.3 mm	Ø 3.3 mm	Ø 3.3 mm
Ø 4.1 mm	Ø 4.1 mm	Ø 4.1 mm	Ø 4.1 mm	Ø 4.1 mm
Ø 4.9 mm	Ø 4.9 mm	Ø 4.9 mm	Ø 4.9 mm	Ø 4.9 mm
Ø 6.2 mm	Ø 6.2 mm	Ø 6.2 mm	Ø 6.2 mm	Ø 6.2 mm